



Discover our TRIPROOF BASIC wet room moisture-proof luminaire. The moisture-proof luminaires are eligible for German federal funding and are particularly energy efficient, which means lower operating costs for your customers. With durable construction and a long service life, the luminaires are very long-lasting. The pre-installed feed-through wiring and the practical cable entry points on the back significantly simplify installation. The metal clips ensure they are secured reliably. We also offer variants with a motion detector, where the brightness threshold, detection range and switch-off delay can be adjusted.

Special features

- Eligible for BEG German federal funding for energy-efficient buildings
- Particularly energy efficient
- Long service life of 50,000 hours L80B50
- Pre-installed feed-through wiring 3x1.5 mm²/5x1.5 mm²
- Cable entry point on the back
- Stainless steel clips on the cover can be locked with screws
- Robust polycarbonate [PC] plastic housing

Housing Material	Polycarbonate, Steel
Housing Color	Grey
Halogen free	Yes
Functions	D marking
Protection Class	Protection class I/protective grounding
Rated Input	20 W
Rated Power Consumption Standby	0.5 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Number of Cable Entries	2 PCS
Cable Gland Diameter	12 mm
Dimmable	No
Motion Detector	No
Light Source	LED, Light source changeable TC
Color Temperature	4000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	2800 lm
Rated Angle of Reflection	120 Degree
Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below
Length	1210 mm
Width	82 mm
Height	75 mm
Working Temperature	-20 to 40 °C
Storage Temperature	-40 to 75 °C
IP Protection Class	IP 65
IK Protection Class	IK08

Life Time L80 / B50	50000 h
Switching Cycles	25000
Power Consumption	20 kWh/1000h
Energy Efficiency Class Lightsource	This product contains a light source of energy efficiency class C.