

## DIN-Signal C/R shroud screw fix 11.75



Image is for illustration purposes only. Please refer to product description.

|                    |                                                                                       |
|--------------------|---------------------------------------------------------------------------------------|
| Part number        | 09 03 000 9960                                                                        |
| Specification      | DIN-Signal C/R shroud screw fix 11.75                                                 |
| HARTING eCatalogue | <a href="https://b2b.harting.com/09030009960">https://b2b.harting.com/09030009960</a> |

### Identification

|                              |                                                            |
|------------------------------|------------------------------------------------------------|
| Category                     | Accessories                                                |
| Series                       | DIN 41612                                                  |
| Type of accessory            | Pin shroud                                                 |
| Description of the accessory | for female connectors type C<br>for male connectors type R |
| Features                     | lead-free                                                  |

### Version

|                    |              |
|--------------------|--------------|
| Termination length | 20 mm        |
| Fixing             | Screw fixing |

### Technical characteristics

|                 |                                      |
|-----------------|--------------------------------------|
| Isolation group | IIIa ( $175 \leq \text{CTI} < 400$ ) |
| PCB thickness   | 3.8 mm $\pm 0.5$                     |

### Material properties

|                                           |                        |
|-------------------------------------------|------------------------|
| Material (accessories)                    | Thermoplastic          |
| Colour (accessories)                      | RAL 7032 (pebble grey) |
| Material flammability class acc. to UL 94 | V-0                    |
| RoHS                                      | compliant              |
| ELV status                                | compliant              |
| China RoHS                                | e                      |
| REACH Annex XVII substances               | Not contained          |



**Pushing Performance**  
Since 1945

## Material properties

|                                      |               |
|--------------------------------------|---------------|
| REACH ANNEX XIV substances           | Not contained |
| REACH SVHC substances                | Not contained |
| California Proposition 65 substances | Yes           |

## Specifications and approvals

|                        |                              |
|------------------------|------------------------------|
| Railway classification | F1/I2 acc. to NFF 16-101/102 |
|------------------------|------------------------------|

## Commercial data

|                                |                                            |
|--------------------------------|--------------------------------------------|
| Packaging size                 | 100                                        |
| Net weight                     | 6.05 g                                     |
| Country of origin              | China                                      |
| European customs tariff number | 85389099                                   |
| GTIN                           | 5713140004399                              |
| eCl@ss                         | 27440292 Connector component (accessories) |