

Han-Compact hood TE/SE M20



Image is for illustration purposes only. Please refer to product description.

Part number	19 12 008 0425
Specification	Han-Compact hood TE/SE M20
HARTING eCatalogue	https://b2b.harting.com/19120080425

Identification

Category	Hoods/Housings
Series of hoods/housings	Han-Compact®
Type of hood/housing	Hood

Version

Size	Han-Compact®
Version	Top/side entry
Cable entry	2x M20
Locking type	Single locking lever
Field of application	Hoods/housings for industrial applications

Technical characteristics

Limiting temperature	-40 ... +125 °C
Degree of protection acc. to IEC 60529	IP65
Type rating acc. to UL 50 / UL 50E	4
	4X
	12

Material properties

Material (hood/housing)	Polycarbonate (PC)
Colour (hood/housing)	RAL 9005 (jet black)
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant



Pushing Performance
Since 1945

Material properties

China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R22 (HL 1-3)
	R23 (HL 1-3)

Specifications and approvals

Approvals	DNV GL
CE	Yes

Commercial data

Packaging size	5
Net weight	33.3 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140124103
eCl@ss	27440202 Shell for industrial connectors