



### Product Features

FTTH-connection set, with wall jack, for surface mounting, with 1xLC-D - coupling (SM/APC), with 70 m cable 4 x E9/125 G657 A2

- connector assembly 1 x LC-D/APC, with integrated laser protection
- 2 inserted reserve fibres (blue/yellow)
- mounting of one microtube 7/4 incl. gas blocker
- for fibre optic cables with a diameter of up to 4.5 mm
- drop cable 4 x E9/125 G657 A2, Ø 2,3 mm, CPR: B2ca-S1, d0, a1
- cable entry from the rear or all 4 sides
- prepared for DIN rail mounting
- clear fibre management in the wall box
- removable, hinged splice tray
- splice tray for max. 4 crimp or shrink splices
- protection class wall mounted: IP50
- temperature range: -10° C - 60° C
- installation material included
- pure white (similar RAL 9010)

### Features

General	
Surface	high-gloss
Classification	OS2 APC (8°)
Protection class IP	50
Halogen Free	Yes
GTIN (EAN)	4043921668306
Mounting types	
surface-mounted	Yes
Dimensions/Weights without packaging	
Length mm	80
Width mm	80
Height mm	31
Certifications	
RoHS conform	Yes
References	
Accessories	228100402, 228100404, 228100406, 228100412
Similar article	228111430, 228111450, 228111470, 228120030, 228120050