



Special features

- Swivel-mounted
- High colour reproduction value
- Dimmable

| | |
|-----------------------------------|---|
| Housing Material | Aluminium |
| Housing Color | White |
| Material of Lens | Plastic |
| Protection Class | Protection class III/safety extra-low voltage |
| Operating Mode | Constant current |
| Rated Input | 13 W |
| Rated Input Voltage | 34.8 V/DC |
| Rated Current | 350 mA |
| Power Supply Unit incl. | No |
| Connection Cable Secondary | Yes |
| Secondary Connection | Open cables |
| Secondary Cable Length | 0.2 m |
| Dimmable | Yes |
| Control technology | Dimmable via optional power supply unit |
| Motion Detector | No |

| | |
|--------------------------------|--------------|
| Product weight | 280 g |
| Working Temperature | -20 to 50 °C |
| Storage Temperature | -20 to 50 °C |
| IP Protection Class | IP 20 |
| Life Time L70 / B50 | 40000 h |
| Switching Cycles | 100000 |
| Power Consumption | 15 kWh/1000h |
| Energy Efficiency Class | F |

| | |
|---|----------------------------------|
| Light Source | LED, Light source not changeable |
| Color Temperature | 3000 K |
| Colour Consistency | 6 SDCM |
| Colour Rendering Index (Ra) | 90 |
| Rated Luminous Flux | 1100 lm |
| Luminous Efficiency | 84.6 lm/W |
| Rated Angle of Reflection | 60 Degree |
| Distribution Characteristic 120° | DLS |

| | |
|------------------------------|--------|
| Light Exit Surfaces | 1 |
| Light characteristics | Direct |
| Light direction | Below |

| | |
|---------------------------|--------|
| Height | 53 mm |
| Diameter | 110 mm |
| Installation Depth | 53 mm |
| Cut Out Diameter | 95 mm |

