

- ① M6 Sicherungsscheibe vom Halterahmen muss verwendet werden
- ① M6 lock washer of the frame has to be used


Anzugsmoment: $10 \pm 1 \text{ Nm}$
 tightening torque: $10 \pm 1 \text{ Nm}$


Wichtiger Hinweis / important notice

Bei der Verwendung mit Han 24HPR enlarged Halterahmen für 4xHan HC Modular 350 verringert sich die Bemessungsspannung nach DIN EN 61 984 auf 2000V -

By using with Han 24HPR enlarged frames for 4xHan HC Modular 350 the rated voltage acc. to DIN EN 61 984 will be reduced to 2000V

Für Han 24HPR enlarged Anbau- und Sockelgehäuse mit Han HC Modular 350
 for Han 24HPR enlarged bulkhead and surface mounting housing with Han HC Modular 350



	All Dimensions in mm Original Size DIN A4	Scale	Free size tol.		Ref.
		2:1			Sub.
All rights reserved Department EL PD - DE	Created by HOLLERT	Inspected by	Standardisation	Date	State
		RIEPE	TIEMANNA	2013-09-19	Final Release
HARTING Electric GmbH & Co. KG D-32339 Espelkamp	Title Guide bushing Han HPR enlarged housing			Doc-Key / ECM-Nr. 100548219/UGD/001/A 500000066455	
	Type	Number		Rev.	Page
TB	09 11 000 9919		A	1/1	