lightnet

Basic-G5

Pendant luminaire - Direct light distribution





Article code: BG5OBL-830H-D800-U

Illustrations may only be similar and serve as an orientation.

Basic-G5. LED. Pendant luminaire. Luminaire body with 38mm visible overall height and minimalist edge of only 5mm. Luminaire body made of high-quality aluminum profile. Surface finish Jet Black. Direct only light distributiColour temperature: 3000K (Warm White). Colour Rendering Index (CRI): >80. Opal diffuser for enhanced light transmission and perfect uniform illumination. Dimmable DALI. DxH (round). D= 800mm. H=38mm. Central cord suspension with ceiling rose and power supply cable (Set). Pendant length max 1500mm. Power supply: transparent.


Ceiling rose: Matching luminaire's surface colour. Highpower current. 6685lm. 54W. 9,5kg. Binning initial <= MacAdam 3. IP40. Protection class I. CE, UKCA marking. Prüfzeichen: ENEC. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,4%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L80B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 and 50001:2018 certified.

lightnet

Basic-G5

Pendant luminaire - Direct light distribution







Article code: BG5OBL-830H-D800-U

Customer / Project:		
Note:		

Productname Basic-G5 Lamp LED

Installation Type Pendant luminaire

Surface finish Jet Black

Colour temperature 3000K

Colour Rendering Index (CRI) CRI>80

Optical system Opal diffuser

Control Dimmable (DALI)

Length L/Diameter D (mm) D=800mm

Height H (mm) H=38mm

Current/Power High-Power

Luminous Flux 6685lm Power consumption 54W

Suspension Central susp. (Set)

Ceiling rose colour Ceiling rose: Matching luminaire's

surface colour

Pendant length (mm) Pendant length max 1500mm

Degree of protection IP40

Certification Prüfzeichen: ENEC

Cable Colour Power supply: transparent LED lifetime L80B10 (tq 25°C) = 50.000h

Photometric code 8 30 / 3 3 9 Photobiological class RG0 (EN62471)

Indoor/Outdoor Indoor: ta [ambient] max. 25°C

Weight (kg) 9,5kg

