



Pushing Performance  
Since 1945

# Han ID Module Socket Profinet



Image is for illustration purposes only. Please refer to product description.

Part number	09 80 615 0200
Specification	Han ID Module Socket Profinet
HARTING eCatalogue	<a href="https://b2b.harting.com/09806150200">https://b2b.harting.com/09806150200</a>

## Identification

Category	Modules
Series	Han-Modular®
Identification	Han-Smart®
Type of module	ID Profinet
Size of the module	Single module
Description of the module	Power supply Data interface with HARTING ix Industrial® (Typ A)
Features	Module for identifying industrial components Profinet I/O communication protocol conformance class B SNMP enabled (V1, V2C)

## Version

Gender	Female
Number of contacts	7
Diagnostic display	Connection (Link) Power connection
Details	GSD software file and operating instructions can be downloaded from the eCatalogue.

## Termination data

Nominal voltage	24 V DC ±10 %
Power consumption	<2 W

## Technical characteristics

Operating temperature	-40 ... +70 °C
-----------------------	----------------



**Pushing Performance**  
Since 1945

## Technical characteristics

Storage temperature	-40 ... +70 °C
Mating cycles	≥500
Degree of protection acc. to IEC 60529	IP20
Real-time class	RT acc. to IEC 61158

## Material properties

Material (insert)	Polycarbonate (PC) Liquid crystal polymer (LCP)
Colour (insert)	RAL 7032 (pebble grey) White
Material flammability class acc. to UL 94	V-0

## Specifications and approvals

Specifications	IEC 60721-3-3 EN 61000-4-2 Electrostatic discharge (ESD) EN 61000-4-3 Electromagnetic field EN 61000-4-4 Rapid transients (burst) EN 61000-4-5 Surge voltages EN 61000-4-6 conducted disturbances IEC 61158
PROFINET	Yes
CE	Yes

## Commercial data

Packaging size	1
Net weight	29.44 g
Country of origin	Germany
European customs tariff number	85366990
GTIN	5713140185074
eCl@ss	27440218 Module for industrial connectors (data)