



#### Special features

- integrated power supply unit for 230V direct connection
- through-wiring possible
- dimmable via leading edge/trailing edge phase
- suitable for 68 mm switch boxes of normal and deep design

<b>Housing Material</b>	Aluminium, Polycarbonate	<b>Working Temperature</b>	-20 to 40 °C
<b>Housing Color</b>	White	<b>Storage Temperature</b>	-40 to 80 °C
<b>Protection Class</b>	Protection class I/protective grounding	<b>IP Protection Class</b>	IP 20
<b>Rated Input</b>	4 W	<b>IK Protection Class</b>	IK05
<b>Rated Power Consumption Standby</b>	0.5 W	<b>Life Time L70 / B50</b>	132000 h
<b>Rated Input Voltage Frequency</b>	220-240 V/AC 50 / 60 Hz	<b>Life Time L80 / B50</b>	84000 h
<b>Power Supply Unit incl.</b>	Yes	<b>Switching Cycles</b>	50000
<b>Number of Cable Entries</b>	3 PCS	<b>Power Consumption EEI</b>	4 kWh/1000h E
<b>Dimmable</b>	Yes		
<b>Control</b>	Leading-edge dimmer, Trailing-edge dimmer		
<b>Motion Detector</b>	No		
<b>Light Source</b>	LED, Light source not changeable		
<b>Color Temperature</b>	2700 K		
<b>Colour Consistency</b>	3 SDCM		
<b>Colour consistency light source</b>	3 SDCM		
<b>Colour Rendering Index (Ra)</b>	80		
<b>Rated Luminous Flux</b>	610 lm		
<b>Luminous Efficiency</b>	129 lm/W		
<b>UGR</b>	19		
<b>Light Exit Surfaces</b>	1		
<b>Light characteristics</b>	Direct		
<b>Light direction</b>	Front		
<b>Height</b>	41 mm		
<b>Diameter</b>	71.5 mm		
<b>Installation Depth</b>	39 mm		
<b>Required Installation Depth</b>	60 mm		
<b>Cut Out Diameter</b>	68 mm		
<b>Product weight</b>	90 g		