



LED wall recessed light WALL KIT68, for device socket  
**Artikel-Nr. 10156083**



LED wall recessed light WALL KIT68, for device socket, black, round. Recessed mounting, Wall-mounted. For installation in cavity wall or concrete device boxes with an installation depth of at least 62 mm (screw distance: 60 mm). Compatible with Kaiser device sockets for cavity wall installation, product no. 9064-02 or 9464-02 or concrete installation, product no. 1556-04. Attention! The delivery is WITHOUT a device socket. Mounting method: Recessed mounting, Place of installation: Wall-mounted, Material: Aluminium / Steel / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) I, Voltage: 230V AC 50Hz, Power: 1.5W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 70lm, Colour temperature: 3.000 K, Light colour : White, With control gear: Yes, Control: on/off.

|             |                  |
|-------------|------------------|
| Artikel-Nr. | 10156083         |
| Stand:      | 07.12.2021 20:04 |

|                                    |                             |
|------------------------------------|-----------------------------|
| Colour temperature                 | 3000 K                      |
| Luminous flux                      | 70 lm                       |
| Amount of light sources / fittings | 1 Qty                       |
| Material                           | Aluminium / Steel / Plastic |
| Power                              | 1,5 W                       |
| Lamp                               | LED                         |
| Colour rendering                   | CRI > 90                    |
| Control                            | on/off                      |
| Built-in diameter                  | 68 mm                       |
| Installation depth                 | 65 mm                       |

|                      |                     |
|----------------------|---------------------|
| Voltage              | 230V AC 50Hz        |
| Circuit type         | Parallel conduction |
| Degree of protection | IP20                |
| Protection class     | I                   |
| Voltage type         | AC                  |
| Length               | 75 mm               |
| Width                | 75 mm               |
| Aufbauhöhe           | 48 mm               |
| Dimensions           | D 75 x H 48 mm      |