



The UNI II series includes high-quality surface-mounted lamps for use on walls and ceilings in commercial and private spaces. The rotatable and swivelling lamp heads have warm white COB LEDs and if required can be folded flush to the mount to shine vertically downwards like a ceiling spotlight. In addition to the single, double and triple designs, there is both a mini version (with smaller lamp head and mount) and a MAX version available. There is also a variant for use in current tracks.

Special features

- Very high colour rendering
- Can be rotated and swivelled
- Dimmable

Housing Material	Die-cast aluminium
Housing Color	White
Material of Lens	Plastic
Protection Class	Protection class I/protective grounding
Rated Input	12 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Type	Clamp
Dimmable	Yes
Control technology	Leading-edge dimmer, Trailing-edge dimmer
Motion Detector	No

IP Protection Class	IP 20
Life Time L70 / B50	20000 h
Switching Cycles	15000
Power Consumption	12 kWh/1000h
Energy Efficiency Class	G

Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	90
Rated Luminous Flux	670 lm
Rated Angle of Reflection	36 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Swivel Angle	90 Degree
Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Height	103 mm
Diameter	100 mm
Base height	14.5 mm
Base diameter	96 mm

Working Temperature	-5 to 40 °C
Storage Temperature	-20 to 50 °C