



The ALWAID 2 recessed wall light fits into any 68 mm standard or deep switch box thanks to its compact design. Furthermore, it does not require an additional power supply. The variety of covers allows you to find a style that suits your space and illuminates your surroundings with beautiful indirect light. The article includes the base only; covers are not included in the scope of delivery.

Special features

- 230 V direct connection
- Feed-through wiring possible
- Can be dimmed using leading-edge phase dimmers or trailing-edge phase dimmers
- Suitable for 68 mm standard and deep switch boxes

Housing Material	Aluminium	Switching Cycles	50000
Housing Color	White	Power Consumption	5 kWh/1000h
Protection Class	Protection class I/protective grounding	Energy Efficiency Class Lightsource	This product contains a light source of energy efficiency class G.
Rated Input	4.8 W		
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz		
Power Supply Unit incl.	Yes		
Connection Type	Clamp		
Dimmable	Yes		
Control	Trailing-edge dimmer		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	4000 K		
Colour Consistency	3 SDCM		
Colour Rendering Index (Ra)	90		
Rated Luminous Flux	230 lm		
Luminous Efficiency	47.9 lm/W		
Rated Angle of Reflection	100 Degree		
UGR	19		
Height	39.9 mm		
Diameter	71.2 mm		
Installation Depth	39.9 mm		
Cut Out Diameter	61.5 mm		
Product weight	71 g		
Working Temperature	-10 to 55 °C		
Storage Temperature	-60 to 20 °C		
IP Protection Class	IP 20		
Life Time L70 / B50	75000 h		
Life Time L80 / B10	50000 h		
Life Time L80 / B50	60000 h		

