

Basic-G1

Pendant luminaire - Direct light distribution

Article code: BG1ASE-830E-D900-P



Illustrations may only be similar and serve as an orientation.



Basic-G1. LED. Pendant luminaire. Luminaire body made of high-quality aluminum profile. Surface finish Radiant Silver. Direct only light distribution. Colour temperature: 3000K (Warm White). Colour Rendering Index (CRI): >80. Microprismatic screen for uniform illumination and reduced luminance in office areas. UGR<=19. Switchable. DxH (round). D=900mm. H=75mm. Rod suspension with ceiling rose (Set). Pendant length on request. Ceiling rose:



Matching luminaire's surface colour. Low-power current. 7405lm. 56W. 12,6kg. Binning initial <= MacAdam 3. IP40. Protection class I. CE, UKCA marking. Prüfzeichen: ENEC. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,2%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L90B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 and 50001:2018 certified.

lightnet

Basic-G1

Pendant luminaire - Direct light distribution

Article code: BG1ASE-830E-D900-P



Customer / Project: _____

Note: _____

Productname	Basic-G1
Lamp	LED
Installation Type	Pendant luminaire
Surface finish	Radiant Silver
Light characteristics	Direct light distribution
Colour temperature	3000K
Colour Rendering Index (CRI)	CRI>80
Optical system	Microprismatic screen
Control	Switchable
Length L/Diameter D (mm)	D=900mm
Height H (mm)	H=75mm
Current/Power	Low-Power
Luminous Flux	7405lm
Power consumption	56W
Suspension	Rod susp. (Set)
Ceiling rose colour	Ceiling rose: Matching luminaire's surface colour
Pendant length (mm)	Pendant length on request
Degree of protection	IP40
Certification	Prüfzeichen: ENEC
LED lifetime	L90B10 (tq 25°C) = 50.000h
UGR	UGR<=19
Photometric code	8 30 / 3 3 9
Photobiological class	RG0 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	12,6kg

