### **BRUMBERG**

## PINOS / AGGY / OREN / TIMOR / CEBU LED driver 800 mA - 1,050 mA, on/off, for through-wiring

Article no. 17840010

Light. For Generations.





#### Tende

LED driver 800 mA - 1,050 mA, on/off, for through-wiring, , Rectangular. Material: Plastic, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 42 W, Dimmable: No, Control: on/off.

Article data	
Article no.	17840010
GTIN	4255752515395
Series name	PINOS / AGGY / OREN / TIMOR / CEBU
Short description	LED driver 800 mA - 1,050 mA, on/off, for through-wiring
Material	Plastic
Shape	Rectangular
Length	170 mm
Width	65 mm
Hight	30 mm
Weight	0.160 kg
stamp	ENEC, EL
Conformance	CE

### **BRUMBERG**

# PINOS / AGGY / OREN / TIMOR / CEBU LED driver 800 mA - 1,050 mA, on/off, for through-wiring

Article no. 17840010

Light. For Generations.

Operating technology of driver	
AC nominal voltage min	198 V
AC nominal voltage max	264 V
Frequency min	50 Hz
Frequency max	60 Hz
DC nominal voltage min	197 V
DC nominal voltage max	278 V
Protection class	II
Power	42 W
Starting current	16,2 A, 294,0us
Suitable for emergency lighting	No
Ambient temperature	-20°C bis +45°C
measure point (tc)	70 °C
Version	ohne Konfektionierung
Power factor	0.95
max. no. lights on B10 A	14
max. no. lights on B16 A	23
max. no. lights on C16 A	39
max. no. lights on C10 A	24
Output voltage max	40.00 V
Output voltage min	25.00 V
Flicker value Pst LM	1.00
Stroboscopic effect value SVM	.40
Control	on/off
Number of poles	3
Flicker-free	Yes
Average nominal lifespan	50000 h
Output current	800, 900, 950 oder 1.050 mA

Packing data	
Gross weight	0.18 kg
Length of packaging	140 mm
Packaging width	110 mm
Packaging hight	120 mm
	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.
Disposal at end of life	By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that
	harmful substances get into the environment.