



The matching DALI pendant luminaires in the LUCEA series for the 3-phase 230 V track system are available in 10 W and offer up to 1,300 lumens of light output. The maximum suspension is 1,600 mm. The beam angle of the individual models can be narrowed or widened using optional lenses. The housing of the Lucea luminaires is made of die-cast aluminium

Special features

- emergency current capable [176-280V/DC EOFI: 100%]
- incl. black reflector ring

Housing Material	Aluminium
Housing Color	Black
Halogen free	No
Functions	Phase switch, Leuchte kann mit Gleichstrom aus einer Zentralbatterie eines Notstromsystems betrieben werden.
Protection Class	Protection class I/protective grounding
Rated Input	10 W
Rated Power Consumption Standby	0.5 W
Rated Input Voltage Frequency	200-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Dimmable	Yes
Control	DALI 2 / DT6, Push-Dim
Motion Detector	No
Voltage range emergency lighting EOFI	176-280 V/DC 100 %

Working Temperature	-20 to 40 °C
Storage Temperature	-20 to 65 °C
IP Protection Class	IP 20
IK Protection Class	IK03

Life Time L70 / B50	50000 h
Life Time L80 / B10	55000 h
Life Time L90 / B10	55000 h
Switching Cycles	100000
Power Consumption	10 kWh/1000h
Energy Efficiency Class Lightsource	This product contains a light source of energy efficiency class E.

Light Source	LED, Light source changeable TC
Lightcolor	Warm white (WW)
Color Temperature	2700 K
Colour Consistency	6 SDCM
Colour consistency light source	3 SDCM
CRI (Ra)	90
Rated Luminous Flux	1300 lm
Rated Angle of Reflection	36 Degree
UGR	12

Width	65 mm
Height	184 mm
Pendulum Length max.	1600 mm
Product weight	540 g