## lightnet

## Basic-P5

Pendant luminaire - Direct/indirect light distribution





Article code: BP5ASE-840M-D600-P

Illustrations may only be similar and serve as an orientation.

Basic-P5. LED. Pendant luminaire. Luminaire body with 38mm visible overall height and minimalist edge of only 5mm.
Luminaire body made of high-quality aluminum profile.
Surface finish Radiant Silver. Direct/indirect light distribution.
Colour temperature: 4000K (Cool White). Colour Rendering Index (CRI): >80. Microprismatic screen for uniform illumination and reduced luminance in office areas. UGR<=19.
Switchable. DxH (round). D=600mm. H=38mm. Rod suspension with ceiling rose (Set). Pendant

length on request. Ceiling rose: Matching luminaire`s surface colour. Medium-power current. 5210lm. 40W. 6,4kg. Binning initial <= MacAdam 3. IP40. Protection class I. CE, UKCA marking. Prüfzeichen: ENEC. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,3%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L85B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 and 50001:2018 certified.

## lightnet


## Basic-P5

Pendant luminaire - Direct/indirect light distribution

Article code: BP5ASE-840M-D600-P







Productname Basic-P5
Lamp LED

Installation Type Pendant luminaire Surface finish Radiant Silver

Light characteristics Direct/indirect light distribution

Colour temperature 4000K Colour Rendering Index (CRI) CRI>80

Optical system Microprismatic screen

Control Switchable
Length L/Diameter D (mm) D=600mm
Height H (mm) H=38mm
Current/Power Medium-Power
Luminous Flux 5210lm

Power consumption 5210 40W

Suspension Rod susp. (Set)

Ceiling rose colour Ceiling rose: Matching luminaire's

surface colour

Pendant length (mm) Pendant length on request

Degree of protection IP40

Certification Prüfzeichen: ENEC

LED lifetime L85B10 (tq  $25^{\circ}$ C) = 50.000h

UGR UGR<=19
Photometric code 8 40 / 3 3 9
Photobiological class RG0 (EN62471)

Indoor/Outdoor Indoor: ta [ambient] max. 25°C

Weight (kg) 6,4kg

























