

## Basic-A5

Surface mounted luminaire - Direct light distribution

Article code: BA5ASE-830M-D400



Illustrations may only be similar and serve as an orientation.





Basic-A5. LED. Surface mounted luminaire for wall or ceiling mounting with minimalist edge. Luminaire body made of high-quality aluminum profile. Surface finish Radiant Silver. Direct only light distribution. Colour temperature: 3000K (Warm White). Colour Rendering Index (CRI): >80. Microprismatic screen for uniform illumination and reduced luminance in office areas. UGR<=19. Switchable. DxH (round). D=400mm. H=38mm. Medium-

power current. 1374lm. 12W. 4,3kg. Binning initial <= MacAdam 3. IP40. Protection class I. CE, UKCA marking. Prüfzeichen: ENEC. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,3%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L85B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 and 50001:2018 certified.

## Basic-A5

Surface mounted luminaire - Direct light distribution

Article code: BA5ASE-830M-D400



Customer / Project: \_\_\_\_\_

Note: \_\_\_\_\_

Productname	Basic-A5
Lamp	LED
Installation Type	Surface mounted luminaire
Surface finish	Radiant Silver
Light characteristics	Direct light distribution
Colour temperature	3000K
Colour Rendering Index (CRI)	CRI>80
Optical system	Microprismatic screen
Control	Switchable
Length L/Diameter D (mm)	D=400mm
Height H (mm)	H=38mm
Current/Power	Medium-Power
Luminous Flux	1374lm
Power consumption	12W
Degree of protection	IP40
Certification	Prüfzeichen: ENEC
LED lifetime	L85B10 (tq 25°C) = 50.000h
UGR	UGR<=19
Photometric code	8 30 / 3 3 9
Photobiological class	RG0 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	4,3kg

