

**Special features**

- Asymmetrical
- Including 1 m connecting cable with WEIPU plug [male]

Housing Material	Stainless steel, Die-cast aluminium
Housing Color	Silver
Material of Lens	Glass
Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Constant voltage
Rated Input	2.7 W
Rated Input Voltage	24 V/DC
Power Supply Unit incl.	No
Connection Cable Secondary	Yes
Secondary Connection	WEIPU plug 2-pole
Secondary Cable Length	1 m
Dimmable	Yes
Control technology	Dimmable via optional controller
Motion Detector	No

Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	110 lm
Luminous Efficiency	40.7 lm/W
Rated Angle of Reflection	45 Degree
Rated Angle of Reflection 2	35 Degree
Light Distribution	Asymetric
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Top

Height	80 mm
Diameter	55 mm
Installation Depth	98 mm

Cut Out Diameter	48 mm
Product weight	308 g
Working Temperature	-20 to 40 °C
Storage Temperature	-10 to 60 °C
IP Protection Class	IP 67
Load Force max.	5 kN
Life Time L70 / B50	25000 h
Switching Cycles	100000
Power Consumption	3 kWh/1000h
Energy Efficiency Class	G