

Panel mounting socket outlet, straight - flange 107x100 fixing centers 85x77




Product description	
BALS-Prd.-Nr	130119
EAN	4024941195409
Product category	TE panel mounting socket outlet Quick-Connect, straight
Current	63A
Number of poles	5p
Poles	3p+N+PE
Position of earth contact	6 h
Voltage	200/346 up to 240/415V

Product description	
Frequency	50 and 60Hz
Protection degree	IP67
Colour code	red RAL 3000
Colour of appliance	Hinged lid red RAL 3000, Bayonet ring grey RAL 7035, Enclosure grey RAL 7035
Connection design	screwless spring terminal with box terminals and kontext-contact
Maximum conductor size	25.0 qmm
Cable entry	other
Height	114mm
Width	111mm
Depth	146mm
Flange size vertical	107mm
Flange size horizontal	100mm
Drill hole distance vertical	85mm
Drill hole distance horizontal	77mm
Material of enclosure	Polyamide
Contact	The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Logistics data	
Weight/pcs	0.665 kg / Piece
Packaging	Bag

Logistics data	
Content amount	1 ST
EAN	4024941195409
Length	146 mm
Width	111 mm
Height	114 mm
Weight	0.666 kg
Volume	1,847.484 ccm
Packaging	Carton
Content amount	5 ST
EAN	4024941958622
Length	295 mm
Width	185 mm
Height	215 mm
Weight	3.489 kg
Volume	9,975 ccm



4 MB 267

Ampere Polzahl	63 4	63 5					
a	107,0	107,0					
b	100,0	100,0					
c	85,0	85,0					
d	77,0	77,0					
e ø	6,5	6,5					
f	12,0	12,0					
h	67,0	67,0					
i	76,0	76,0					
k	113,0	113,0					
l ø	88,0	88,0					
m	7,0	7,0					
Leiter mm² min	6	6					
Leiter mm² max	25	25					