



**Special features**

- Including connecting cable

<b>Housing Material</b>	Stainless steel
<b>Housing Color</b>	Silver
<b>Material of Lens</b>	Glass
<b>Protection Class</b>	Protection class III/safety extra-low voltage
<b>Operating Mode</b>	Constant voltage
<b>Rated Input</b>	21.6 W
<b>Rated Input Voltage</b>	24 V/DC
<b>Power Supply Unit incl.</b>	No
<b>Connection Cable Secondary</b>	Yes
<b>Secondary Connection</b>	WEIPU plug 4-pole
<b>Secondary Cable Length</b>	0.5 m
<b>Dimmable</b>	Yes
<b>Control technology</b>	Dimmable via optional controller
<b>Motion Detector</b>	No

<b>Working Temperature</b>	-20 to 40 °C
<b>Storage Temperature</b>	-10 to 60 °C
<b>IP Protection Class</b>	IP 67
<b>IK Protection Class</b>	IK07
<b>Load Force max.</b>	20 kN
<b>Life Time L70 / B50</b>	35000 h
<b>Switching Cycles</b>	20000
<b>Power Consumption</b>	22 kWh/1000h

<b>Light Source</b>	LED, Light source not changeable
<b>Rated Luminous Flux</b>	340 lm
<b>Luminous Efficiency</b>	15.7 lm/W
<b>Rated Angle of Reflection</b>	30 Degree
<b>Light Distribution</b>	Symmetric

<b>Light Exit Surfaces</b>	1
<b>Light characteristics</b>	Direct
<b>Light direction</b>	Top

<b>Length</b>	549 mm
<b>Width</b>	68 mm
<b>Height</b>	32.5 mm
<b>Installation Depth</b>	80 mm
<b>Cut Out Length</b>	524 mm
<b>Cut Out Width</b>	58 mm
<b>Product weight</b>	2723 g