

connector domestic type - with hinged lid and increased contact protection (Shutter), System F German standard



Product description	
BALS-Prd.-Nr	748709-1
EAN	4024941429184
Product category	Domestic connector
Current	16A
Number of poles	3p
Arrangement of phases	2P+PE
Voltage	250V~
Frequency	AC

Product description	
Protection degree	IP54
Colour code	blue RAL 5015
Colour of appliance	Housing cover black/grey, Hinged lid black RAL 9005, Cable gland black RAL 9005, Collar black RAL 9005
Connection design	head-screw terminal
Maximum conductor size	4,0 qmm
Cable entry	with cable gland
Height	129mm
Width	64mm
Depth	52mm
Material of enclosure	Polyamide
Contacts	the contacts are brass nickel plated, The contact carrier is made of polyamide

Additional technical properties	
	with german earthing system, With increased contact protection (shutter)
	With rubberized housing cover (SUSTAINABLE-GRIP), MULTI-GRIP cable gland with gasket and integrated strain relief, The enclosure components are connected without screws and are secured by a snap slider. Opening is only possible using a screwdriver., With rubberized cable gland (SUSTAINABLE-GRIP)
	With self-closing hinged lid

Logistics data	
Weight/pcs	0.102 kg / Piece
Packaging	Bag
Content amount	1 ST
Length	52 mm
Width	64 mm
Height	129 mm
Weight	0.103 kg
Volume	409.344 ccm
Packaging	Carton
Content amount	20 ST
Length	245 mm
Width	177 mm
Height	185 mm
Weight	2.173 kg
Volume	7,140 ccm







