

HARTING F+B Hybridcable, PO 50m



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 09 45 600 0335 |
| Specification | HARTING F+B Hybridcable, PO 50m |
| HARTING eCatalogue | https://b2b.harting.com/09456000335 |

Identification

| | |
|---------------|------------------------------|
| Category | System cabling |
| Element | Bulk cables |
| Specification | Not assembled |
| Type of cable | Hybrid cable (copper/copper) |

Version

| | |
|-----------------|-------------------------|
| Cable length | 50 m |
| Number of cores | 13 |
| Core structure | 2x 2x AWG 22 |
| | 2x 0.75 mm ² |
| | 2x 1.5 mm ² |
| | 5G 2.5 mm ² |

Technical characteristics

| | |
|------------------------------|---------------------------------------|
| Transmission characteristics | Cat. 5e Class D up to 100 MHz |
| Data rate | 10 Mbit/s |
| | 100 Mbit/s |
| Limiting temperature | -40 ... +90 °C |
| Minimum bending radius | 10x Cable diameter (repeated bending) |

Material properties

| | |
|------------------|----------------------|
| Material (cable) | Polyolefin copolymer |
| Colour (cable) | Black |



Pushing Performance
Since 1945

Specifications and approvals

| | |
|-----------|-----------------------|
| Approvals | Ecolab Topactive 200 |
| | Ecolab Topactive 500 |
| | Ecolab Topax 66 |
| | Ecolab Topax 990 |
| | Ecolab Topactive OKTO |

Commercial data

| | |
|--------------------------------|-----------------------|
| Packaging size | 1 |
| Net weight | 391 g/m |
| Country of origin | Germany |
| European customs tariff number | 85444995 |
| GTIN | 5713140273993 |
| eCl@ss | 27060501 Hybrid cable |