



## Recessed ceiling spot

Article no. 2392.15



### Tender

Recessed ceiling spot, nickel, Round. In a compact design, for installation in tool-less rapid assembly systems. Lamp holder: GX5.3, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Cast iron / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Voltage: 12V, Power: 50 W, Amount of light sources / fittings: 1 piece, without control gear, Type of dimming: Depending on driver.

Article data	
Article no.	2392.15
GTIN	4250047762409
Short description	Recessed ceiling spot
Material	Cast iron / Plastic
Colour	nickel
Type of surface	Matt
Shape	Round
Outer diameter	80 mm
Built-in diameter min.	68 mm
Built-in diameter max.	68 mm
Installation depth	80 mm
Weight	0.08 kg
D licence plate	No
Conformance	CE, UKCA



## Recessed ceiling spot

Article no. 2392.15

Operating technology of the luminaire	
System output	50 W
Voltage type	AC/DC
AC nominal voltage max	12 V
Frequency max	50 Hz
Lamp	For LED-retrofill lamp
Lamp holder	GX5.3
Protection class	III
Degree of protection	IP20
Control	Depending on driver
Energy efficiency class	not required

Mounting technology	
Mounting method	Recessed mounting
Place of installation	Ceiling-mounted
Further references	No cover with thermal insulation material

Packing data	
Gross weight	0.11 kg
Length of packaging	90 mm
Packaging width	55 mm
Packaging height	109 mm
Disposal at end of life	<p>This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.</p> <p>By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.</p>

Compatible LED-modu-							
Article no.	Power	Beam angle	Colour temperature	Colour rendering		Input	Hight LED-Modul
12925003	3 W	38°	2.700 K	CRI > 80		350 mA	40 mm