lightnet

Matric-A3

Surface mounted light-line - Direct light distribution





Article code: LA3LBL-840H-L1002-B

Illustrations may only be similar and serve as an orientation.

Matric-A3. LED. Wall or ceiling mounted light-line. Luminaire body made of high-quality aluminum profile. Surface finish Jet Black. Direct only light distribution. Colour temperature: 4000ÿ (Cool White). Colour Rendering Index (CRI): >80. Lens Louvre: precision lenses with louvre. High glare limitation, compatiblefor office applications. Reflector: Jet Black. Dimmable DALI. LxWxH (rectangular). L= 1002mm. W=55mm. H=75mm. High-

power current. 3590lm. 28W. 2,9kg. Binning initial <= MacAdam 3. IP20. Protection class I. CE, UKCA marking. Prüfzeichen: ENEC. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,4%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L80B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated

lightnet


Matric-A3


Surface mounted light-line - Direct light distribution

Article code: LA3LBL-840H-L1002-B









Custome	er / Projec	et:		
Note:				

Productname Matric-A3 Lamp LED

Installation Type Surface mounted light-line

Surface finish Jet Black

Light characteristics Direct light distribution

4000K Colour temperature Colour Rendering Index (CRI) CRI>80 Optical system Lens Louvre Reflector Colour Inside Reflector: Jet Black Control Dimmable (DALI) Length L/Diameter D (mm) L=1002mm Width W (mm) W=55mm Height H (mm) H=75mm Current/Power High-Power

Luminous Flux 3590lm
Power consumption 28W
Degree of protection IP20

Certification Prüfzeichen: ENEC

LED lifetime L80B10 (tq 25° C) = 50.000h

Photometric code 8 40 / 3 3 9 Photobiological class RG0 (EN62471)

Indoor/Outdoor Indoor: ta [ambient] max. 25°C

Weight (kg) 2,9kg

