

R 15-EGW-13,5



Part number	09 15 000 0102
Specification	R 15-EGW-13,5
HARTING eCatalogue	https://b2b.harting.com/09150000102

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Hoods/Housings
Series	R 15
Type of hood/housing	Screw mounted housing
Description of hood/housing	Angled
Version	
Locking type	Screw locking
Technical characteristics	
Limiting temperature	-40 +125 °C
Degree of protection acc. to IEC 60529	IP65
Material properties	
Material (hood/housing)	Polycarbonate (PC)
Material (hood/housing) Material (seal)	Polycarbonate (PC) NBR
Material (seal)	NBR
Material (seal) RoHS	NBR compliant with exemption
Material (seal) RoHS RoHS exemptions	NBR compliant with exemption 6(c): Copper alloy containing up to 4 % lead by weight
Material (seal) RoHS RoHS exemptions ELV status	NBR compliant with exemption 6(c): Copper alloy containing up to 4 % lead by weight compliant with exemption
Material (seal) RoHS RoHS exemptions ELV status China RoHS	NBR compliant with exemption 6(c): Copper alloy containing up to 4 % lead by weight compliant with exemption 50
Material (seal) RoHS RoHS exemptions ELV status China RoHS REACH Annex XVII substances	NBR compliant with exemption 6(c): Copper alloy containing up to 4 % lead by weight compliant with exemption 50 Not contained

Page 1 / 2 | Creation date 2022-08-18 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



Material properties

California Proposition 65 substances	Yes
California Proposition 65 substances	Lead Nickel Naphthalene
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R22 (HL 1-3) R23 (HL 1-3)
Commercial data	

Packaging size10Net weight29.16 gCountry of originGermanyEuropean customs tariff number85389099GTIN5713140021600eCl@ss27440224 Shell for circular connectors

Page 2 / 2 | Creation date 2022-08-18 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com