Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or	trade mark:	SPECTRUM
--------------------	-------------	----------

Supplier's address: Wojnarowscy, Gospodarcza 16 40-432 Katowice Poland

Model identifier: WOJ+14379

_	•			
Type	Λt	liont	COLL	rca.
IVDC	v	HIGHL	30 U	ı cc.

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	E27		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with spe- cific dimmers

Product parameters

Froduct parameters				
Parameter		Value	Parameter	Value
		General product p	arameters:	
<u> </u>	nption in on- 00 h), rounded st integer	6	Energy efficiency class	G
dicating if it refe a sphere (360º) (120º) or in a na	s flux (фuse), in- ers to the flux in , in a wide cone rrow cone (90º)	500 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode pow pressed in W	ver (P _{on}), ex-	6,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
(P _{net}) for CLS, 6	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	82
Outer dimen-	Height	83	Spectral power dis-	See image
sions without	Width	45	tribution in the	in last page
separate con- trol gear, light-	Depth	45	range 250 nm to 800 nm, at full-load	

ing control parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equival	ent power ^(a)	Yes	If yes, equivalent power (W)	41	
			Chromaticity coordi-	0,383	
			nates (x and y)	0,380	
Parameters for LED and OLED light sources:					
R9 colour rende	ring index value	17	Survival factor	0,90	
the lumen maintenance factor		0,96			
Parameters for	Parameters for LED and OLED mains light sources:				
displacement fa	ctor (cos φ1)	0,90	Colour consistency in McAdam ellipses	5	
Claims that an L replaces a flu source without last of a particul	orescent light integrated bal-	_(b)	If yes then replace- ment claim (W)	-	
Flicker metric (P	st LM)	0,5	Stroboscopic effect metric (SVM)	0,2	

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

