



Abbildung ähnlich

Product Features

LC-D/LC-D patch cord, OM3, aqua, 5m

- MM-fibre, G50/125 Åm, grade C3 or SM-Faser E9/125Åm, grade C1
- low insertion loss
- latch for connector locking
- pre-polished ceramic ferrule, 1,25 mm
- with kink protection sleeves
- life > 1000 cycles
- 5 m

Features

General

Design	plug, ceramic sleeve
Classification	OM3
Halogen Free	Yes
Country of manufacture	CN
GTIN (EAN)	4043921665008
Dimensions/Weights without packaging	
Cable length mm	5.000
Cable diameter mm	3
Cable construction	50/125µm, Grade C3
Net weight piece kg	0,034

Certifications

RoHS conform	Yes
--------------	-----

Logistics Information

Packaging	polybag
Packaging unit Quantity	1
Packaging unit Weight kg	0,04
Packaging unit Width mm	180
Packaging unit Height mm	210
Packaging unit Depth mm	20

References

Accessories	228030006, 228030012, 228030024, 228030106, 228030112, 228030124, 228030206, 228030212, 228030224, 228030306, 228030312, 228030324, 228030406, 228030412, 228030424
-------------	---

Similar article

	228050002, 228050105, 228050205, 228050305, 228050405, 228050505, 228050905, 228051305
--	--