

Connector - with TE screw terminals, for harsh applications



Product description	
BALS-Prd.-Nr	3193
EAN	4024941031936
Product category	Connector TE
Current	125A
Number of poles	4p
Poles	3P+PE
Position of earth contact	4 h
Voltage	100 up to 130V

Product description	
Frequency	50 and 60Hz
Protection degree	IP67
Colour code	yellow RAL 1012
Colour of appliance	Hinged lid yellow RAL 1012, Bayonet ring grey RAL 7035, Housing cover grey RAL 7035, Cable gland grey RAL 7035, Collar grey RAL 7035
Connection design	screw terminal as box terminal with Kontex-contact
Maximum conductor size	50.0 qmm
Cable entry	Cable gland
Height	295mm
Width	125mm
Depth	128mm
Material of enclosure	Polyamide
Contact	The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Additional technical properties	
	For cable diameter from 26 up to max. 50 mm, Multi-Grip cable gland with gasket, integrated cable clamp and additional water evacuation openings

Logistics data	
Weight/pcs	1.23 kg / Piece
Packaging	Bag
Content amount	1 ST

EAN	4024941031936
Length	128 mm
Width	125 mm
Height	295 mm
Weight	1.231 kg
Volume	4,720 ccm
Packaging	Carton
Content amount	5 ST
EAN	4024941835374
Length	345 mm
Width	345 mm
Height	217 mm
Weight	6.485 kg
Volume	24,276 ccm

