




YLIP LED wall surface mounted luminaire, IP65
Article no. 10131183



Tender
LED wall surface mounted luminaire, IP65, Oval. Luminaire length 180.0 mm, Luminaire width 70.0 mm, Hight 95.0 mm Weight 0.902 kg, with rotationssymmetrical, deep, wide distributed light intensity. Cover glass transparent. Luminous flux 1.390 - 1.640 lm, Power 1 x 15 W, Light colour warm white to daylight white, Correlated color temprature (CCT) 3.000 - 5.700 K, Colour rendering index CRI > 80, Housing material: Aluminium / Glass, Colour: black structure, Permissible ambient temperature (ta): -20 to +45°C, Protection class (EN 61140): I, Degree of protection (DIN EN 60529): IP65, shock resistance according to IEC62262: IK06 .With electronic driver, on/off switchable.

Article data	
Article no.	10131183
GTIN	4251433971818
Series name	YLIP
Short description	LED wall surface mounted luminaire, IP65
Material	Aluminium / Glass
Colour	black structure
Type of surface	Structure
Shape	Oval
Length	180 mm
Width	70 mm
Hight	95 mm
Scope of delivery	Incl. converter for connection to the 230-V mains voltage, on/off switchable
Weight	0.902 kg
Conformance	CE, UKCA


YLIP LED wall surface mounted luminaire, IP65

Article no. 10131183

Lighting technology	
Colour temperature	3.000 K / 4.000 K / 5.700 K
Light colour	white
Color Temperature 1	3,000 K
Color Temperature 2	4,000 K
Color Temperature 3	5,700 K
Light output	Direct/Indirect
Luminous flux	1,390 - 1,640 lm
Luminous flux 1	1,390 lm
Luminous flux 2	1,640 lm
Luminous flux 3	1,500 lm
System efficiency	109 lm/W
Colour rendering	CRI > 80
Luminaire optics	Lens
Reflector	Without
Beam angle	45°
Light sharing	Symmetric
Adjustable color temperature	Stages

Operating technology of the luminaire	
System output	15 W
Voltage type	AC
AC nominal voltage max	230 V
Frequency max	50 Hz
Frequency min	50 Hz
Lamp	LED
Lamp holder	Without fitting
Protection class	I
Degree of protection	IP65
Ambient temperature	-20 to +45°C
Control	on/off
Bulb change possible	The light source of this luminaire may only be replaced by the manufacturer or a service technician commissioned by him or a similarly qualified person.
Energy efficiency class	not required

Mounting technology	
Mounting method	Surface mounting
Place of installation	Wall-mounted
Adjustability	Not adjustable
Impact resistance	IK06
Material cover	Glass transparent
Suitable for through-wiring	Yes

Packing data	
Gross weight	1.036 kg
Length of packaging	215 mm
Packaging width	105 mm
Packaging height	135 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.