lightnet

Ringo Star-P3

Pendant luminaire - Direct/indirect light distribution







Article code: RP3OBE-830M-D1500-K

Ringo Star-P3. LED. Pendant luminaire. Luminaire body made of aluminium profile with 60mm track width. Surface finish Jet Black. Direct/indirect light distribution. Colour temperature: 3000K (Warm White). Colour Rendering Index (CRI): >80. Opal diffuser for enhanced light transmission and perfect uniform illumination. Switchable. DxHxW (round). D=1500mm. W=60mm. H=85mm. Cord suspension for parallel installation with power supply cable and ceiling rose (Set). Pendant length max 4000mm.

Power supply: transparent. Ceiling rose: Matching luminaire`s surface colour. Medium-power current. 18289lm. 175W. 15,9kg. Binning initial <= MacAdam 3. IP20. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,3%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L85B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 and 50001:2018 certified.

lightnet


Ringo Star-P3

Pendant luminaire - Direct/indirect light distribution

Article code: RP3OBE-830M-D1500-K







Productname Ringo Star-P3
Lamp LED

Installation Type Pendant luminaire

Surface finish Jet Black

Light characteristics Direct/indirect light distribution

3000K Colour temperature CRI>80 Colour Rendering Index (CRI) Optical system Opal diffuser Control Switchable Length L/Diameter D (mm) D=1500mm Width W (mm) W=60mm Height H (mm) H=85mm Current/Power Medium-Power Luminous Flux 18289lm Power consumption 175W

Suspension Parallel susp. (Set)

Ceiling rose colour Ceiling rose: Matching luminaire`s

surface colour

Pendant length (mm) Pendant length max 4000mm

Degree of protection IP2

Cable Colour Power supply: transparent

LED lifetime L85B10 (tq 25° C) = 50.000h Photometric code $8\ 30\ /\ 3\ 3\ 9$ Photobiological class RG0 (EN62471)

Indoor/Outdoor Indoor: ta [ambient] max. 25°C

Weight (kg) 15,9kg



min. 200

max. 4000























