lightnet

Ringo Star-G3

Pendant luminaire - Direct light distribution





Article code: RG3OSL-840H-D600-K

Illustrations may only be similar and serve as an orientation.

Ringo Star-G3. LED. Pendant luminaire. Luminaire body made of aluminium profile with 60mm track width. Surface finish Radiant Silver. Direct only light distribution. Colour temperature: 4000K (Cool White). Colour Rendering Index (CRI): >80. Opal diffuser for enhanced light transmission and perfect uniform illumination. Dimmable DALI. DxHxW (round). D=600mm. W=60mm. H=85mm. Cord suspension for parallel installation with power supply cable and ceiling rose (Set). Pendant length max 4000mm. Power supply:


transparent. Ceiling rose: Matching luminaire`s surface colour. High-power current. 4300lm. 53W. 6kg. Binning initial <= MacAdam 3. IP20. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,4%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L80B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 and 50001:2018 certified.

lightnet

Ringo Star-G3

Pendant luminaire - Direct light distribution







Article code: RG3OSL-840H-D600-K

Customer / Project:		
Note:		

Productname Ringo Star-G3

Lamp LED

Installation Type Pendant luminaire Surface finish Radiant Silver

Light characteristics Direct light distribution Colour temperature 4000K

Colour temperature 4000K
Colour Rendering Index (CRI) CRI>80
Optical system Opal diffuser
Control Dimmable (DALI)
Length L/Diameter D (mm) D=600mm
Width W (mm) W=60mm
Height H (mm) H=85mm

Width W (mm) W=60mm
Height H (mm) H=85mm
Current/Power High-Power
Luminous Flux 4300lm
Power consumption 53W

Suspension Parallel susp. (Set)

Ceiling rose colour Ceiling rose: Matching luminaire`s

surface colour

Pendant length (mm) Pendant length max 4000mm

Degree of protection IP20

Cable Colour Power supply: transparent
LED lifetime L80B10 (tq 25°C) = 50.000h

Photometric code 8 40 / 3 3 9 Photobiological class RG0 (EN62471)

Indoor/Outdoor Indoor: ta [ambient] max. 25°C

Weight (kg) 6kg

