


Art. no. 950020

Pendant lamp Lautaro 600/60 Down Opal P3, 37 W,
DALI, 2700 K, white

 **DEKOLIGHT**



| | | | |
|--|---|--|--|
| Housing Material | Aluminium, Steel | Life Time L70 / B50 | 180000 h |
| Housing Color | White | Life Time L80 / B10 | 120000 h |
| Material of Lens | Polycarbonate - PC | Life Time L80 / B50 | 130000 h |
| Surface Structure of Lens | Opal | Life Time L90 / B10 | 50000 h |
| | | Life Time L90 / B20 | 60000 h |
| Protection Class | Protection class I/protective grounding | Switching Cycles | 100000 PCS |
| Rated Input | 37 W | Power Consumption | 37 kWh/1000h |
| Rated Power Consumption Standby | 0.3 W | Energy Efficiency Class Lightsource | This product contains a light source of energy efficiency class E. |
| Rated Input Voltage | 198-264 V/AC | | |
| Dimmable | Yes | | |
| Control | DALI 2 / DT6, Push-Dim | | |
| Light Source | LED, Light source changeable TC | | |
| Color Temperature | 2700 K | | |
| Colour Consistency | 3 SDCM | | |
| Colour consistency light source | 2 SDCM | | |
| CRI (Ra) | 90 | | |
| Rated Luminous Flux | 4450 lm | | |
| Rated Angle of Reflection | 90 Degree | | |
| UGR | 22 | | |
| Light Exit Surfaces | 1 PCS | | |
| Light characteristics | Direct | | |
| Light direction | Below | | |
| Height | 60 mm | | |
| Diameter | 600 mm | | |
| Pendulum Length max. | 3000 mm | | |
| Working Temperature | -20 to 50 °C | | |
| Storage Temperature | -40 to 80 °C | | |
| IP Protection Class Lamp | IP 20 | | |
| IK Protection Class | IK05 | | |