

plug - with screwless terminals, for harsh applications





Product description	
BALS-Prd.-Nr	210766-1
EAN	4024941402927
Product category	QUICK-CONNECT TE plug
Current	63A
Number of poles	5p
Arrangement of phases	3p+N+PE
Position of earth contact	6 h
Voltage	200/346 - 240/415V~
Frequency	50/60Hz

Product description	
Protection degree	IP67
Colour code	red RAL 3000
Colour of appliance	Collar red RAL 3000, Pusher black RAL 9005, Housing cover dark grey RAL 7012, Cable gland dark grey RAL 7012, Bajonet ring dark grey RAL 7012
Connection design	screwless spring-clamp technology with box terminals
Maximum conductor size	16,0 qmm
Cable entry	with cable gland
Material of enclosure	Polyamide
Contacts	The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Additional technical properties	
	For cable diameter from 16 up to max. 36 mm, Screwless housing connection, With rubberized cable gland (SUSTAINABLE-GRIP), With rubberized bayonet ring (SUSTAINABLE-GRIP), Multi-Grip cable gland with gasket and integrated strain relief

Logistics data	
Weight/pcs	0.792 kg / Piece
Packaging	Bag
Content amount	1 ST
EAN	4024941402927
Length	114 mm
Width	114 mm

Logistics data	
Height	234 mm
Weight	0.793 kg
Volume	3,041.064 ccm
Packaging	Carton
Content amount	5 ST
EAN	4024941402934
Length	325 mm
Width	217 mm
Height	210 mm
Weight	4.166 kg
Volume	13,588.4 ccm



Ampere Polzahl	63 3	63 4	63 5
ø a	114,0	114,0	114,0
b	153,0	153,0	153,0
d	171,0	171,0	171,0
ø e	36,0	36,0	36,0
x	233,0	233,0	233,0
y	114,0	114,0	114,0
z	114,0	114,0	114,0
Cond. mm² min	6,0	6,0	6,0
Cond. mm² max	16,0	16,0	16,0



