

Ringo Star-G5

Pendant luminaire - Direct light distribution

Article code: RG5LBL-830H-D370-PB-BP



Illustrations may only be similar and serve as an orientation.


Ringo Star-G5. LED. Pendant luminaire. Luminaire body made of aluminium profile with 40mm profile width. Surface finish Jet Black. Direct only light distribution. Colour temperature: 3000K (Warm White). Colour Rendering Index (CRI): >80. Lens Louvre: precision lenses with louvre for wide and symmetrical light distribution. High glare limitation, compatible for office applications. UGR<=19. Reflector: Jet Black. Blind Plate. Dimmable DALI. DxHxW (round). D= 370mm. W=40mm. H=40mm. Rod suspension

with ceiling rose (Set). Pendant length on request. Ceiling rose: Matching luminaire`s surface colour. High-power current. 3871lm. 34W. 4kg. Binning initial <= MacAdam 3. IP20. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,4%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L80B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated

Ringo Star-G5

Pendant luminaire - Direct light distribution

Article code: RG5LBL-830H-D370-PB-BP



Customer / Project: _____

Note: _____

| | |
|------------------------------|---|
| Productname | Ringo Star-G5 |
| Lamp | LED |
| Installation Type | Pendant luminaire |
| Surface finish | Jet Black |
| Light characteristics | Direct light distribution |
| Colour temperature | 3000K |
| Colour Rendering Index (CRI) | CRI>80 |
| Optical system | Lens Louvre |
| Reflector Colour Inside | Reflector: Jet Black |
| Central Module | Blind Plate |
| Control | Dimmable (DALI) |
| Length L/Diameter D (mm) | D=370mm |
| Width W (mm) | W=40mm |
| Height H (mm) | H=40mm |
| Current/Power | High-Power |
| Luminous Flux | 3871lm |
| Power consumption | 34W |
| Suspension | Rod susp. (Set) |
| Ceiling rose colour | Ceiling rose: Matching luminaire`s surface colour |
| Pendant length (mm) | Pendant length on request |
| Degree of protection | IP20 |
| LED lifetime | L80B10 (tq 25°C) = 50.000h |
| UGR | UGR<=19 |
| Photometric code | 8 30 / 3 3 9 |
| Photobiological class | RG0 (EN62471) |
| Indoor/Outdoor | Indoor: ta [ambient] max. 25°C |
| Weight (kg) | 4kg |

