

**Product Features**

Mounting adapter, 1-way, DIN-rail mounting, for holding a universal modular jack UM-Cat.6A iso 25/10G or UM-Cat.6A iso 40/10G on a DIN-rail, light grey (similar RAL 7035)

- for one universal module UM-Cat.6A iso 25/10G or UM-Cat.6A iso 40/10G
- insulation class II (without earth connection)
- insulation class I (with earth connection)
- for DIN-rail mounting (18 mm)
- earthing connection at the modular jack via customary blade terminal
- RJ45 - slanted outlet (ca. 45°)
- with labelling field

**Features**

General	
Design	adapter
Labeling field	Yes
Protection class IP	20
Halogen Free	Yes
Statistical goods number	85389099
Country of manufacture	DE
GTIN (EAN)	4043921666890
Mounting types	
DIN-Rail	Yes
Dimensions/Weights without packaging	
Length mm	17,8
Width mm	71
Height mm	73,2
Certifications	
RoHS conform	Yes
References	
Accessories	13900308, 13900310, 17000600, 17000601, 17000604, 17000605, 17000606, 17000607, 17000608, 17000609, 17010052, 17010650, 17010651, 17010653, 17010657, 228080000, 228080100, 228080200, 228080300, 228080400, 228080500, 228080600, 228080700, 228080800, 228080900, 228081000, 228081200, 228081300