

## Han 48HPR-Deckel (ohne Kabeleingang)



Image is for illustration purposes only. Please refer to product description.

Part number	09 40 048 9803
Specification	Han 48HPR-Deckel (ohne Kabeleingang)
HARTING eCatalogue	<a href="https://b2b.harting.com/09400489803">https://b2b.harting.com/09400489803</a>

### Identification

Category	Hoods/Housings
Series of hoods/housings	Han <sup>®</sup> HPR
Type of hood/housing	Mounting cover
Description of hood/housing	Distance bolt M5

### Version

Size	48 B
Locking type	Screw locking
Field of application	Hoods/housings for harsh outdoor environments
Pack contents	4 distance pieces 4x M6 screw 4 washers

### Technical characteristics

Tightening torque (screw locking)	4 Nm
Limiting temperature	-40 ... +125 °C
Degree of protection acc. to IEC 60529	IP65 IP68 IP69 / IPX9K acc. to ISO 20653

### Material properties

Material (hood/housing)	Aluminium die-cast Corrosion resistant
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 9005 (jet black)



Pushing Performance  
Since 1945

## Material properties

Material (seal)	NBR
Material (locking)	Stainless steel
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol
California Proposition 65 substances	Yes
California Proposition 65 substances	Nickel Naphthalene

## Specifications and approvals

Approvals	DNV GL
-----------	--------

## Commercial data

Packaging size	1
Net weight	612.04 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140058385
eCl@ss	27440208 Cap for industrial connectors