


## Matric-AX

Surface mounted light-line - Direct light distribution

Article code: LAXLEE-840E-L1723-A



Illustrations may only be similar and serve as an orientation.



Matric-AX. LED. Wall or ceiling mounted light-line. Luminaire body made of high-quality aluminum profile. Surface finish Silver Anodised. Direct only light distribution. Colour temperature: 4000K (Cool White). Colour Rendering Index (CRI): >80. Lens Louvre: precision lenses with louvre for wide and symmetrical light distribution. High glare limitation, compatible for office applications. UGR<=19. Reflector: Satin Silver. Switchable. LxWxH (rectangular). L=

1723mm. W=40mm. H=65mm. Low-power current. 2910lm. 22W. 3,3kg. Binning initial <= MacAdam 3. IP20. Protection class I. CE, UKCA marking. Prüfzeichen: ENEC. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,2%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L90B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 and 50001:2018 certified.

## Matric-AX

Surface mounted light-line - Direct light distribution

Article code: LAXLEE-840E-L1723-A



Customer / Project: \_\_\_\_\_

Note: \_\_\_\_\_

|                              |                                |
|------------------------------|--------------------------------|
| Productname                  | Matric-AX                      |
| Lamp                         | LED                            |
| Installation Type            | Surface mounted light-line     |
| Surface finish               | Silver Anodised                |
| Light characteristics        | Direct light distribution      |
| Colour temperature           | 4000K                          |
| Colour Rendering Index (CRI) | CRI>80                         |
| Optical system               | Lens Louvre                    |
| Reflector Colour Inside      | Reflector: Satin Silver        |
| Control                      | Switchable                     |
| Length L/Diameter D (mm)     | L=1723mm                       |
| Width W (mm)                 | W=40mm                         |
| Height H (mm)                | H=65mm                         |
| Current/Power                | Low-Power                      |
| Luminous Flux                | 2910lm                         |
| Power consumption            | 22W                            |
| Degree of protection         | IP20                           |
| Certification                | Prüfzeichen: ENEC              |
| LED lifetime                 | L90B10 (tq 25°C) = 50.000h     |
| UGR                          | UGR≤19                         |
| Photometric code             | 8 40 / 3 3 9                   |
| Photobiological class        | RG0 (EN62471)                  |
| Indoor/Outdoor               | Indoor: ta [ambient] max. 25°C |
| Weight (kg)                  | 3,3kg                          |

