

Han1A CA 3+PE -lever m/- PVC 5m



Image is for illustration purposes only. Please refer to product description.

Part number	33 50 020 0201 050
Specification	Han1A CA 3+PE -lever m/- PVC 5m
HARTING eCatalogue	https://b2b.harting.com/33500200201050

Identification

Category	System cabling
Series	Han [®] 1A
Element	Cable assemblies
Specification	Pre-assembled on one side
Connector 1	Han [®] 1A Male
Type of cable	Copper cable (round)
Description of the cable	Oil resistant

Version

Cable length	5 m
Number of cores	4
Core structure	4x 2.5 mm ²
Number of contacts	3
PE contact	Yes
Locking type	Single locking lever

Technical characteristics

Rated current	16 A
Rated voltage	400 V
Rated voltage conductor-earth	300 V
Limiting temperature	-40 ... +80 °C unmoved -15 ... +80 °C moved
Mating cycles	≥100



Pushing Performance
Since 1945

Technical characteristics

Degree of protection acc. to IEC 60529	IP65
Cable diameter	9.2 mm

Material properties

Material (cable)	PVC
Colour (cable)	Grey

Specifications and approvals

Specifications	IEC 60332-1-2 Flame retardancy
----------------	--------------------------------

Commercial data

Packaging size	1
Net weight	850 g
Country of origin	Romania
European customs tariff number	85444290
GTIN	5713140237117
eCl@ss	27060311 Assembled sensor actuator-line