

Wall mounting appliance inlet - with external fixing



| Product description | |
|---------------------------|---|
| BALS-Prd.-Nr | 242002 |
| EAN | 4024941019286 |
| Product category | Wall mounting appliance inlet Quick-Connect |
| Current | 32A |
| Number of poles | 5p |
| Poles | 3p+N+PE |
| Position of earth contact | 6 h |
| Voltage | 200/346 up to 240/415V |
| Frequency | 50 and 60Hz |

| Product description | |
|------------------------|---|
| Protection degree | IP44 |
| Colour code | red RAL 3000 |
| Colour of appliance | Housing top red RAL 3000, Collar red RAL 3000, Housing bottom grey RAL 7035 |
| Connection design | screwless spring-clamp technology |
| Maximum conductor size | 6,0 qmm |
| Cable entry | top entry M25 |
| Height | 133mm |
| Width | 94mm |
| Depth | 87mm |
| Dimension of enclosure | 92x94 mm (HxW) |
| Material of enclosure | Polyamide |
| Contact | The contact carrier is made of polyamide, The contacts are brass |

| Additional technical properties | |
|---------------------------------|---|
| | The cable entry is one at top open and one at bottom closed |

| Logistics data | |
|----------------|------------------|
| Weight/pcs | 0.272 kg / Piece |
| Packaging | Bag |
| Content amount | 1 ST |
| EAN | 4024941019286 |

| Logistics data | |
|----------------|---------------|
| Length | 87 mm |
| Width | 94 mm |
| Height | 133 mm |
| Weight | 0.273 kg |
| Volume | 1,087.674 ccm |
| Packaging | Carton |
| Content amount | 10 ST |
| EAN | 4024941958196 |
| Length | 325 mm |
| Width | 217 mm |
| Height | 210 mm |
| Weight | 2.926 kg |
| Volume | 13,588.4 ccm |



5 MB 44

| Ampere | 16 | 16 | 16 | 32 | 32 | 32 |
|----------------------------|-------|-------|-------|-------|-------|-------|
| Polzahl | 3 | 4 | 5 | 3 | 4 | 5 |
| a | 59,5 | 72,4 | 72,4 | 79,1 | 79,1 | 79,1 |
| b | 90,0 | 90,0 | 90,0 | 92,0 | 92,0 | 92,0 |
| c | 120,0 | 120,0 | 122,0 | 134,0 | 134,0 | 134,0 |
| d | 72,0 | 84,0 | 84,0 | 89,0 | 89,0 | 89,0 |
| e | 62,0 | 77,0 | 77,0 | 84,0 | 84,0 | 84,0 |
| f | 33,5 | 33,5 | 33,5 | 30,0 | 30,0 | 30,0 |
| h | 9,0 | 9,0 | 9,0 | 9,0 | 9,0 | 9,0 |
| i | 5,5 | 5,5 | 5,5 | 5,5 | 5,5 | 5,5 |
| k | 8,0 | 9,0 | 9,0 | 9,0 | 9,0 | 9,0 |
| l ø | 21,0 | 21,0 | 21,0 | 21,0 | 21,0 | 21,0 |
| m | 72,0 | 87,0 | 87,0 | 94,0 | 94,0 | 94,0 |
| n | M20 | M25 | M25 | M25 | M25 | M25 |
| Leiter mm ² min | 1 | 1 | 1 | 2,5 | 2,5 | 2,5 |
| Leiter mm ² max | 2,5 | 2,5 | 2,5 | 6 | 6 | 6 |