

## Plank-P4

Pendant luminaire - Direct/indirect light distribution

Article code: JP4AEL-840H-L1500-Y



Illustrations may only be similar and serve as an orientation.



Plank-P4. LED. Pendant luminaire. Luminaire body made of high-quality aluminum profile. Surface finish Silver Anodised. Direct/indirect light distribution. Colour temperature: 4000K (Cool White). Colour Rendering Index (CRI): >80. Microprismatic screen for uniform illumination and reduced luminance in office areas. UGR≤19. Dimmable DALI. LxWxH (rectangular). L=1500mm. W=231mm. H=25mm. Y-cord suspension with power supply cable and ceiling rose (Set). Pendant length max 1500mm.

Power supply: transparent. Ceiling rose: Matching luminaire's surface colour. High-power current. 7540lm. 64W. 9,3kg. Binning initial ≤ MacAdam 3. IP20. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,4%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L80B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated

## Plank-P4

Pendant luminaire - Direct/indirect light distribution

Article code: JP4AEL-840H-L1500-Y



Customer / Project: \_\_\_\_\_

Note: \_\_\_\_\_

Productname	Plank-P4
Lamp	LED
Installation Type	Pendant luminaire
Surface finish	Silver Anodised
Light characteristics	Direct/indirect light distribution
Colour temperature	4000K
Colour Rendering Index (CRI)	CRI>80
Optical system	Microprismatic screen
Control	Dimmable (DALI)
Length L/Diameter D (mm)	L=1500mm
Width W (mm)	W=231mm
Height H (mm)	H=25mm
Current/Power	High-Power
Luminous Flux	7540lm
Power consumption	64W
Suspension	Y-susp. (Set)
Ceiling rose colour	Ceiling rose: Matching luminaire's surface colour
Pendant length (mm)	Pendant length max 1500mm
Degree of protection	IP20
Cable Colour	Power supply: transparent
LED lifetime	L80B10 (tq 25°C) = 50.000h
UGR	UGR<=19
Photometric code	8 40 / 3 3 9
Photobiological class	RG0 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	9,3kg

