

## Han 3A M Receptacle AC set




Image is for illustration purposes only. Please refer to product description.

Part number	09 57 368 0500 000
Specification	Han 3A M Receptacle AC set
HARTING eCatalogue	<a href="https://b2b.harting.com/09573680500000">https://b2b.harting.com/09573680500000</a>

### Identification

Category	Connectors
Series	RJ45 Hybrid
Element	Panel feed through

### Version

Size	Han <sup>®</sup> 3 A
Shielding	Fully shielded, 360° shielding contact
Number of contacts	8
Contact configuration	L1, PE, N
further contacts	+ 3x 300 V AC

### Technical characteristics

Conductor cross-section	0.08 ... 0.22 mm <sup>2</sup> Stranded
Conductor cross-section	AWG 28 ... AWG 24 Stranded
Transmission characteristics	Cat. 5 Class D up to 100 MHz
Data rate	10 Mbit/s 100 Mbit/s 1 Gbit/s 2.5 Gbit/s
Limiting temperature	-40 ... +70 °C

### Material properties

RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight



Pushing Performance  
Since 1945

## Material properties

ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
California Proposition 65 substances	Yes
California Proposition 65 substances	Antimony trioxide Lead Nickel Naphthalene
Requirement set with Hazard Levels	R26

## Specifications and approvals

Approvals	DNV GL
-----------	--------

## Commercial data

Packaging size	1
Net weight	89 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140072541
eCl@ss	27440101 Rectangular connectors (set)