

## M17 FE str molded 6+PE PVC open end,10m



Image is for illustration purposes only. Please refer to product description.

|                    |   |
|--------------------|---|
| Part number        | 21 37 520 0703 100  |
| Specification      | M17 FE str molded 6+PE PVC open end,10m   |
| HARTING eCatalogue | <a href="https://b2b.harting.com/21375200703100">https://b2b.harting.com/21375200703100</a> |

### Identification

|               |                                    |
|---------------|------------------------------------|
| Category      | System cabling                     |
| Series        | Circular connectors M17            |
| Element       | Cable assemblies                   |
| Specification | Pre-assembled on one side          |
| Connector 1   | M17 Overmoulded<br>Female Straight |
| Type of cable | Copper cable (round)               |

### Version

|                 |  |
|-----------------|--|
| Cable length    | 10 m                                       |
| Number of cores | 7  |
| Core structure  | 6x 0.5 mm <sup>2</sup> + 1 mm <sup>2</sup> |

### Technical characteristics

|  |                |
|--|----------------|
| Rated current                          | 8 A            |
| Rated voltage                          | 300 V          |
| Limiting temperature                   | -20 ... +80 °C |
| Degree of protection acc. to IEC 60529 | IP65<br>IP67   |

### Material properties

|                  |       |
|------------------|-------|
| Material (cable) | PVC   |
| Colour (cable)   | Black |



**Pushing Performance**  
Since 1945

## Commercial data

|                                |   |
|--------------------------------|---|
| Packaging size                 | 1                                       |
| Country of origin              | China                                   |
| European customs tariff number | 85444290                                |
| GTIN                           | 5713140240773                           |
| eCl@ss                         | 27060311 Assembled sensor actuator-line |