

Panel mounting socket outlet - flange 75x75, fixing centers 60x60, straight execution




Product description	
BALS-Prd.-Nr	4359
EAN	4024941043595
Product category	Panel mounting socket outlet, extra-low voltage, straight
Current	16A
Number of poles	2p
Poles	2P
Position of earth contact	10 h
Voltage	20 up to 25 and 40 up to 50V

Product description	
Frequency	direct current (DC)
Protection degree	IP44
Colour code	gray RAL 7035
Colour of appliance	Hinged lid grey RAL 7035, Enclosure grey RAL 7035
Connection design	with screw terminal
Maximum conductor size	10,0 qmm
Cable entry	other
Height	76mm
Width	75mm
Depth	61mm
Flange size vertical	75mm
Flange size horizontal	75mm
Drill hole distance vertical	60mm
Drill hole distance horizontal	60mm
Material of enclosure	Polyamide
Contact	The contact carrier is made of polyamide, the contacts are brass nickel plated

Logistics data	
Weight/pcs	0.127 kg / Piece
Packaging	Bag
Content amount	1 ST

Logistics data	
EAN	4024941043595
Length	61 mm
Width	75 mm
Height	76 mm
Weight	0.128 kg
Volume	347.7 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941971102
Length	207 mm
Width	162 mm
Height	142 mm
Weight	1.37 kg
Volume	3,750 ccm

 16 MB 47	Ampere	16	16	32	32		
	Polzahl	2	3	2	3		
	a	75,0	75,0	75,0	75,0		
	b	75,0	75,0	75,0	75,0		
	c	60,0	60,0	60,0	60,0		
	d	60,0	60,0	60,0	60,0		
	e ø	5,2	5,2	5,2	5,2		
	f	6,0	6,0	6,0	6,0		
	h	22,0	22,0	22,0	22,0		
	i	37,0	37,0	37,0	37,0		
	k	67,0	67,0	67,0	67,0		
	l ø	49,0	49,0	49,0	49,0		
	m	2,0	2,0	2,0	2,0		
	Leiter mm² min	4	4	4	4		
	Leiter mm² max	10	10	10	10		